

	1	2	3	4	5	6	7	8	9																	
A	<div>Part No: RAC004</div>			<div>RoHS COMPLIANT 2011/65/EC</div>																						
	<div>Customer Ref:</div>																									
	<div>Quotation No: Q7778</div>																									
B	<div></div>																									
C				<table><tr><th>No</th><th>Description</th><th>Colr</th><th>Dia mm</th></tr><tr><td>1</td><td><b>Strength Member</b> Continuous Filament Aramid &amp; Polyester High Tenacity yarn 10,080 dTex + 6,600 dTex</td><td>YW</td><td>1.40 Nom</td></tr><tr><td>2</td><td><b>Conductor</b> Tinned Copper Wire Braid 16/8/0.10mm BS EN 13602:2002 Min 95% Optical Coverage</td><td>N/A</td><td>1.80 +/- 0.20</td></tr><tr><td>3</td><td><b>Jacket</b> PVC Type 4 C54/45 Minimum 0.50mm RTI RAL 6020 Chrome Green</td><td>GN</td><td>3.20 +/- 0.10</td></tr></table>							No	Description	Colr	Dia mm	1	<b>Strength Member</b> Continuous Filament Aramid & Polyester High Tenacity yarn 10,080 dTex + 6,600 dTex	YW	1.40 Nom	2	<b>Conductor</b> Tinned Copper Wire Braid 16/8/0.10mm BS EN 13602:2002 Min 95% Optical Coverage	N/A	1.80 +/- 0.20	3	<b>Jacket</b> PVC Type 4 C54/45 Minimum 0.50mm RTI RAL 6020 Chrome Green	GN	3.20 +/- 0.10
				No	Description	Colr	Dia mm																			
1	<b>Strength Member</b> Continuous Filament Aramid & Polyester High Tenacity yarn 10,080 dTex + 6,600 dTex	YW	1.40 Nom																							
2	<b>Conductor</b> Tinned Copper Wire Braid 16/8/0.10mm BS EN 13602:2002 Min 95% Optical Coverage	N/A	1.80 +/- 0.20																							
3	<b>Jacket</b> PVC Type 4 C54/45 Minimum 0.50mm RTI RAL 6020 Chrome Green	GN	3.20 +/- 0.10																							
D				<table><tr><th colspan="2">Notes</th></tr><tr><td><b>Electrical Characteristics</b> Nominal Conductor Resistance Minimum Insulation Resistance</td><td>20.20 Ω/KM @ 20°C &gt;500 MΩ/KM @ 1000V</td></tr><tr><td><b>Mechanical Characteristics</b> Maximum Operating Temp Minimum Cold Bend Temp Minimum Cold Flex Temp  Minimum Break Load Minimum Break Force  Maximum Elongation @ 20°C  Minimum Recommended Bend Radius  Nominal Weight</td><td>+100°C -60°C -40°C  90 KGF 0.8826 kN  2% @ 660 N  5.60 mm  15.50 g/m</td></tr></table>							Notes		<b>Electrical Characteristics</b> Nominal Conductor Resistance Minimum Insulation Resistance	20.20 Ω/KM @ 20°C >500 MΩ/KM @ 1000V	<b>Mechanical Characteristics</b> Maximum Operating Temp Minimum Cold Bend Temp Minimum Cold Flex Temp  Minimum Break Load Minimum Break Force  Maximum Elongation @ 20°C  Minimum Recommended Bend Radius  Nominal Weight	+100°C -60°C -40°C  90 KGF 0.8826 kN  2% @ 660 N  5.60 mm  15.50 g/m										
				Notes																						
<b>Electrical Characteristics</b> Nominal Conductor Resistance Minimum Insulation Resistance	20.20 Ω/KM @ 20°C >500 MΩ/KM @ 1000V																									
<b>Mechanical Characteristics</b> Maximum Operating Temp Minimum Cold Bend Temp Minimum Cold Flex Temp  Minimum Break Load Minimum Break Force  Maximum Elongation @ 20°C  Minimum Recommended Bend Radius  Nominal Weight	+100°C -60°C -40°C  90 KGF 0.8826 kN  2% @ 660 N  5.60 mm  15.50 g/m																									
<div>Page 1 of 1</div>																										
	02	Revise weight to actuals	AJK	17/03/21	PKR	17/03/21	<div>This document is the property of Concept Cables Ltd and must not be copied, modified, re-printed or otherwise disclosed to any third party without written permission</div>		<div></div>		TITLE High Power Flexible Dipole Antenna															
01	Issue Part Code	CH	10/12/13			DESCRIPTION																				
00	Quotation	SMO	26/11/13			CUSTOMER																				
ISSUE	DESCRIPTION	DRWN	DATE	APPD	DATE																					